Mainsail	2 reefs. 3 short leach battens. Marline hitched to gaff & boom. Laced to mast	Not	tes:
Staysail	Hanked to forestay. Loose footed.	1.	A
Roller jib	Set on Wykeham-Martin roller gear Size 2. Provided with Ø6 s/s wire luff for direct connection to roller gear and to replace m/head forestay.	2.	R
M/head forestay	Replaced by wire luff in roller jib. Tension between roller gear and bowsprit fitting with lanyard (Ø5 polyester line, minimum six turns)		
Int. forestay	Ø6 1 x 19 s/s wire. Top end Talurit hard end with 8mm s/s D-shackle. Bottom end Talurit hard eye to Norseman 671-3\8 rigging screw.		
Shrouds	Ø6 1 x 19 s/s wire. Top end Talurit hard end with 8mm D-shackle. Bottom end Talurit hard eye to Norseman 671-3\8 rigging screw.		
Runners (optional)	Ø4 7 x 7 s/s wire with Ø8 polyester rope tails spliced on. Talurit hard eye each end of wire. Top ends attached to top mast band with Ø6 s/s D-shackles.		
Bobstay	Ø6 1 x 19 s/s wire with Talurit hard eye each end. Ø8 s/s D-shackle to lower fitting. Set up at top end with lanyard (Ø5 polyester line, minimum six turns).		
Bowsprit shrouds	Ø6 1 x 19 s/s wire with Talurit hard eye each end. Ø8 s/s D-shackle to bowsprit end. Set up at inner ends with lanyards (Ø5 polyester line, minimum six turns).		
Peak halyard	Ø10 polyester through masthead sheave.		
Throat halyard	Ø10 polyester through single block hung athwartships on 4-eye band at hounds. Block Main size 4 single reversible shackle (4-RS).		
Staysail halyard	Ø10 polyester through single block hung athwartships on 4-eye band at hounds. Block Main size 4 single reversible shackle (4-RS).		
Jib halyard	Ø10 polyester through single block hung athwartships on 4-eye band at head. Block Main size 4 single block reversible shackle (4-RS).		
Main sheet	Ø10 polyester. Main size 4 double block swivel head (4D-SE) hung on boom.		
Staysail sheet	Ø10 polyester. Main size 4 single block swivel head (4-SE) hung on boom.		
Jib sheets	Ø10 polyester.		
Topping lift	Ø8. Main size 3 single block swivel head (3-SE) hung on 4-eye band at head.		
	Roach 150 2400		0
	each 8865		0

s:

- All dimensions are in millimetres unless otherwise noted.
- Refer also to spar drawings, spar metalwork drawings & deck plan.

