

	Aft face of frame			Fwd face of frame		
	Position	Offset	Height	Position	Offset	Height
COACHROOF						
Centreline	-3000	0	1348	-2975	0	1347
b 100	-3000	100	1346	-2975 -2975	100	1347
b 200	-3000	200	1346	-2975 -2975	200	1338
b 300		300	1329	-2975 -2975		1328
b 400	-3000 -3000	400	1314		300 400	1314
b 500		500	1296	-2975 2075		1295
b 600	-3000 -3000	600	1296	-2975 -2975	500	1290
					600	
b 700 b 800	-3000 -3000	700	1249 1221	-2975 -2975	700 800	1249 122
		800	1200			120
Roof edge	-3000	868	1200	-2975	867	1200
SIDEDECK						
Inside of deck	-3000	868	819	-2975	867	820
Outside of deck (sheer)	-3000	1046	771	-2975	1046	77
Catolac of acolt (chicol)	0000	1010		2010	1010	
HULL						
Sheer	-3000	1046	771	-2975	1046	77.
wl 600	-3000	1038	600	-2975	1037	60
wl 400	-3000	1017	400	-2975	1015	40
wl 200	-3000	966	200	-2975	964	20
dwl	-3000	860	0	-2975	857	
b 800	-3000	800	-65	-2975	800	-6
b 700	-3000	700	-140	-2975	700	-13
b 600	-3000	600	-192	-2975	600	-19
b 500	-3000	500	-231	-2975	500	-23
b 400	-3000	400	-263	-2975	400	-26
b 300	-3000	300	-290	-2975	300	-28
b 200	-3000	200	-314	-2975	200	-31
b 100	-3000	100	-335	-2975	100	-33
Rebate	-3000	50	-345	-2975	50	-34

- The Zero Point is the intersection of the dwl with the stem at the forefoot.
- The (fore-&-aft) centreline is marked c/line.
- Offsets are measured about centreline.
- Heights are measured above or below (marked "-") the dwl.
- Positions are measured forward and aft (marked "-") of the Zero Point.
- Offsets on diagonals are measured along the diagonal.
- Waterlines are marked "wl" followed by their height.
- Buttock lines are marked "b" followed by their offset.
- Diagonals are marked "d" followed by their height on the centreline and then their angle to it.
- All offsets are to inside ofskin unless otherwise noted.



support@whisstock.com

**Boat 123** 

Frame -3000

Scale	1/10 & 1/2
Date	18/10/2000
Plan No.	123/004/04
Issue No.	01 web

All dimensions in millimetres unless noted otherwise

© bmarkweb Ltd 2002 All Rights Reserved