



Note: Fit lower rudder pintle before cleaning off rounding of leading edge nose. Rounding may need to be modified in way of pintle. See Rudder plans.

Note: Skeg chock bonds to fwd face of skeg and butts up under hog.

General Notes:

1. All measurements and dimensions are in millimetres unless noted otherwise.
2. The Zero Point is the fwd face of the stem at top of deck.
3. The (fore-&-aft) centreline is marked "C/line".
4. Offsets are measured about centreline.
5. Heights are measured above or below (marked "-") the dwl.
6. Positions are measured forward and aft (marked "-") of the Zero Point.
7. Offsets on diagonals are measured along the diagonal.
8. Waterlines are marked "wl" followed by their height.
9. Buttock lines are marked "b" followed by their offset.
10. Diagonals are marked "d" followed by their height on the centreline and then their angle to it.
11. All offsets are to inside ofskin unless otherwise noted.

 <p><b>Whisstock</b> boats and boat plans</p>	support@whisstock.com	
	<p><b>Boat 074</b></p> <p><b>Modified Structures (Outboard Motor)</b></p> <p><b>Profile View</b></p>	
© Bmarkweb Ltd 2007 All Rights Reserved		<p>Scale 1/10</p> <p>Date 05/08/2008</p> <p>Plan No. 074/003/07</p> <p>Issue No. 2008/01</p> <p>All dimensions in millimetres unless noted otherwise</p>