



Specific Notes:

1. Dropboards are made from 9mm + 4mm ply bonded together; top & bottom edges can be solid mahogany trimmed if wished.
2. Top edge of top board is shaped to suit curve of underside of hatch - leave 1-5mm gap between hatch and dropboard.
3. Drop boards are WEST bonded and coated.
4. Lock is SL 1913300 mounted on 7mm thick pad on inside on top board, shooting up into hatch.
5. Rebate pieces etc. all solid mahogany, WEST bonded & coated.
6. Rebate on board edges at join of boards can be 6 x 6 as shown or 6 x 9 & 6 x 4 (on top of lower board) if wished to form rebate by ply thicknesses.

Notes:

1. The Zero Point is the front of the stem at underside of deck at the sheer.
2. The (fore-&-aft) centreline is marked c/line.
3. Offsets are measured about centreline.
4. Heights are measured above or below (marked "-") the dwl.
5. Positions are measured forward and aft (marked "-") of the Zero Point.
6. Offsets on diagonals are measured along the diagonal.
7. Waterlines are marked "wl" followed by their height.
8. Buttock lines are marked "b" followed by their offset.
9. Diagonals are marked "d" followed by their height on the centreline and then their angle to it.
10. All offsets are to inside of skin unless otherwise noted.

 Whisstock boats and boat plans	support@whisstock.com	
	Boat 119	Scale 1/10 & 1/2
Companionway	Date 20/05/2000	
	Plan No. 119/009/03	
	Issue No. 01 web	
	All dimensions in millimetres unless noted otherwise	
© bmarkweb Ltd 2002 All Rights Reserved		